Onaseal

Sealing strips & custom rubber profiles · www.onasealrubber.com

Edge trim with side bulb: C-series size chart (14 sections)

The C-series edge trim with side bulb has 14 standard sections. Grip range runs from 0.5–2 mm (C-17A) to 2.5–7 mm (C-24B) and bulb height from 5 mm to 15 mm. Choose the model whose grip range covers your panel thickness and whose bulb is slightly taller than the gap, then quote by model number.

Model	Grip range	Bulb height	Groove depth	Compresses to
C-14	1–2	6	10	10
C-14A	1.5–3	5	8	10
C-14C	1–2	5	10	10
C-15	1.5–3	5	10	10
C-15A	1–2.5	8	10	9
C-17	1–2	7	10	11
C-17A	0.5–2	8	7	10
C-20	1–2	9	10	11
C-20A	1–2.5	11	10	11
C-22	1.5–4	11	15	12
C-24A	2–4.5	14	14	13
C-24B	2.5–7	11	14	14
C-25	2–3.5	14	14	13
C-25A	1.5–3	15	13	12

All sizes in mm. Grip range = panel thickness the channel holds; compresses to = bulb height when the door is closed.

Ordering

No minimum – orders from 10 m · Sampling 7–10 days · Stock items ship within 7 days · Packing: 100 m or 150 m per roll, usually 4 rolls per carton; custom packing on request · Terms: FOB, CIF, EXW, DDP

Quote: send the model or section, length and colour to dora@onaseal.com or WhatsApp +86 159 2054 4735. Online chart: https://www.onasealrubber.com/profile-library/bulb-edge-trim-c-series/

Facts last reviewed 2026-11-02. Sizes are nominal; confirm the section with a sample before mass production.